

Box Scrapers

TRACTOR PTO HP RANGE: UP TO 45 HP

GBC48 | 48-inch **BSS54** | 54-inch
BSS60 | 60-inch **BSS65** | 65-inch
BSS72 | 72-inch

- Three-point hitch: Limited 1, and 1
- Designed for sub-compact and compact tractors
- Hardened scarifier teeth with replaceable tips
- Reversible/replaceable high-carbon cutting edges



BSS72

TRACTOR PTO HP RANGE: 40 - 65 HP

BSM72 | 72-inch
BSM84 | 84-inch

- Three-point hitch: CAT 1 and 2
- End plates: .5-inch– 33% heavier end plates than our BSS models
- One-quarter-inch plate welded inside of end plates to increase life
- Optional floating, hinged tailgate to provide maximum downforce on cutting edge

MODEL	GBC48	BSS54	BSS60	BSS65	BSS72	BSM72	BSM84
Tractor Engine HP Range	up to 25 hp		up to 45 hp			40–65 hp	
Tractor Hitch	Ltd 1 & 1		CAT 1			CAT 1 & 2	
Working Width	48"	54"	60"	65"	72"	72"	84"
Capacity	6.8' cubic	10.3' cubic	11.5' cubic	12.5' cubic	13.8' cubic	13.8' cubic	16.2' cubic
Approximate Weight	285 lbs	486 lbs	514 lbs	528 lbs	551 lbs	680 lbs	750 lbs
Scarifier Depth	0"–1.5"		0", 1.5" or 3" adjustable				
Number of Scarifiers	4	4	5	5	6	6	7
Tailgate Type	fixed					fixed, floating optional	
Reversible Cutting Edge (qty/size)	(2) 0.5" x 6"						

Grading Scrapers



Ideal for leveling, from filling driveway potholes to removing a soil berm. Woods grading scrapers are designed to handle more material in fewer passes.

- Heavy-duty mast plates create more downforce for smoother surface and virtually eliminates washboard effect
- Adjustable skid shoes and scarifiers increase performance
- Tall side frames hold more material
- Approachable leading edges and structural reinforcements keep scraper stronger for longer
- Reversible/replaceable high-carbon cutting edges



GSS72P

GSS72

TRACTOR PTO HP RANGE: 15 - 45 HP

- GSS54/GSS54P** | 53-inch
- GSS60/GSS60P** | 59-inch
- GSS72/GSS72P** | 71-inch

- Three-point hitch: Limited CAT 1 and 1
- Fourteen- and sixteen-inch box heights

TRACTOR PTO HP RANGE: 30 - 65 HP

- GSM84/GSM84P** | 83-inch
- GSM96/GSM96P** | 95-inch

- Three-point hitch: CAT 1 and 2
- Sixteen-inch box height — one of the tallest in the industry

MODEL	GSS54/ GSS54P	GSS60/ GSS60P	GSS72/ GSS72P	GSM84/ GSM84P	GSM96/ GSM96P
Tractor Engine HP Range	15–30 hp	20–45 hp		30–65 hp	
Hitch Category	Limited CAT 1 & 1	CAT 1		CAT 1 & 2	
Working Width	53"	59"	71"	83"	95"
Overall Width	58"	64"	76"	88"	100"
Overall Length	42"	46"			
Box Height	14"	16"			
Weight without Scarifiers	349 lbs	493 lbs	580 lbs	664 lbs	712 lbs
Weight with Scarifiers*	409 lbs	553 lbs	655 lbs	754 lbs	802 lbs
Number of Scarifiers*	4		5	6	
Reversible Cutting Edge (qty/size)	(2) 0.5" x 6"				
Scarifier Adjustments*	-4.0, -2.5, -1.0, +1.0	-2.5, -1.0, +0.5, +2.5			
Skid Shoe Adjustment	-0.75 to +0.75		-1.0 to +0.5		
Lower Hitch Design	clevis				

* NOTE: Premium Models only: GSS54P, GSS60P, GSS72P, GSM84P, GSM96P

Rear Blades

Ideal for grading dirt or gravel, cleaning up construction sites and moving snow.

TRACTOR HP RANGE: UP TO 45 HP

RBS54 | 53-inch

RBS60P | 59-inch

RBS60 | 59-inch

RBS72P | 71-inch

RBS72 | 71-inch

RBS84P | 83-inch

- Formed moldboard made from high-strength steel provides exceptional rigidity and pivots 360°
- Double-beveled, reversible, bolt-on cutting edge adds to product life and enables easy replacement
- Optional skid shoes for depth control, and optional parking stand for easier attachment

TRACTOR HP RANGE: 30 - 65 HP 50 - SERIES REAR BLADES

RB72.50 | 71-inch

RB84.50 | 83-inch

RB96.50 | 95-inch

- Seventeen-inch high, ¼-inch thick moldboard
- Double-beveled, reversible and hardened cutting edge for long life
- Fully manual offers angle, offset and tilt adjustments
- Optional end plates, skid shoes and hydraulic angle kit (includes relief valve)
- Convenient parking stand is standard



RB72.50

Rear Blades

TRACTOR HP RANGE: 40 - 85 HP 60 - SERIES REAR BLADES

RB84.60 | 83-inch

RB96.60 | 95-inch

- Seventeen and a half-inch high, 5/16-inch thick moldboard
- Double-beveled, reversible and hardened cutting edge for long life
- Choose manual or hydraulic, featuring angle, offset and tilt adjustments
- Optional end plates, skid shoes, tailwheel and selector valve
- Convenient parking stand is standard

TRACTOR HP RANGE: 50 - 100 HP

RB750 | 83-inch

RB850 | 95-inch

- Three-point hitch: CAT 2
- Seventeen-inch high, reinforced moldboard
- Optional end plates, skid shoes and tailwheel
- Standard parking stand



Rear Blades



RBS84P
Shown with optional parking stand

MODEL	RBS54	RBS60	RBS72	RBS60P	RBS72P	RBS84P	RB72.50	RB84.50	RB96.50
Tractor Engine HP	up to 30 hp			20-45 hp			30-65 hp		
Tractor Hitch	Limited CAT 1 & 1			CAT 1			CAT 1 & 2		
Working Width	53"	59"	71"	59"	71"	83"	71"	83"	95"
Moldboard Height	12"			15"			17"		
Moldboard Thickness	0.182" (grade 80 steel)			0.125" (grade 80 steel)			0.25" (grade 80 steel)		
Weight	134 lbs	142 lbs	156 lbs	268 lbs	288 lbs	308 lbs	455 lbs	475 lbs	495 lbs
Double-beveled, Reversible Cutting Edge Dimensions	0.375" x 6"			0.5" x 6"			0.5" x 6"		
Angle Adjustments	5 positions up to 30°						7 positions up to 45° (mech or hyd)		
Offset Adjustments	—	—	—	up to 12" left or right			6", 12", 18" left or right		
Tilt Adjustments	—	—	—	up to 15°			5 positions up to 23°		
End Plates	—	—	—	optional			optional		
Skid Shoes	optional						optional		
Tailwheel	—	—	—	—	—	—	—		
Parking Stand	optional						standard		
ASABE Quick-Hitch Compatible	yes						yes		

Rear Blades



RB96.60
Shown with optional hydraulic adjustment and selector valve

RB84.60	RB96.60	RB750	RB850	RB990	RB1010
40-85 hp		50-100 hp		80-150 hp	
CAT 1 & 2		CAT 2		CAT 2 & 3	
83"	95"	83"	95"	107"	119"
17.5"		17"		18"	
0.313"		0.313"		0.25"	
705 lbs	730 lbs	1,193 lbs	1,233 lbs	1,483 lbs	1,535 lbs
0.5" x 6"		0.5" x 6"			
up to 45° (mech or hyd)		9 forward up to 60°; 5 reverse up to 30° (mech or hyd)		up to 60° (hyd)	
up to 20° (mech or hyd)		up to 24° (mech or hyd)		up to 33° (mech or hyd)	
up to 23° (mech or hyd)		up to 30° (mech or hyd)		up to 28° (mech or hyd)	
optional		optional		—	—
optional		optional		—	—
optional		optional			
standard		standard			
yes		yes			