

MF 2600 H SERIES A MODERN CLASSIC

45-75 HP





FOR HARDWORKING PEOPLE LOOKING FOR A HARDWORKING TRACTOR.

The Massey Ferguson 2600 H Series is a rugged line of straightforward and dependable utility tractors that offer the heritage and affordability of classic Massey Ferguson models. These tractors feature everything you expect in a Massey Ferguson, starting with a simple, open-platform design. A steel hood, fenders and platform offer rugged durability while the high-capacity hydraulics enable loader and implement work.

VERSATILE — Whether you farm, landscape or contract, the MF 2600 H Series will help you get work done.

Transmission — Choose between an 8F x 2R with live PTO or an 8F x 8R shuttle with independent PTO.

STABLE — MF 2600 H Series tractors combine innovation with confidence-building stability. It all adds up to a tough tractor that's ready to go when you are.

COMFORTABLE — Even if you don't need all the bells and whistles, you still want a comfortable ride. The MF 2600 H Series delivers.

EASY TO USE — The MF 2600 H Series makes everything easier for the operator.

No DPF — No diesel particulate filter (DPF). No regenerations. No downtime.

No DEF — Does not require the use of diesel exhaust fluid (DEF).

Serviceability — A simple release hood latch makes preventative maintenance, like checking filters and fluid levels, easy.





STRAIGHTFORWARD VALUE.

PARTS & SERVICE

IT'S ALL ABOUT A LIFETIME OF SUPPORT

Buying, owning and maintaining equipment can be complex. That's why ensuring you have support and peace of mind is always an important consideration. With Massey Ferguson, you can count on personalized, responsive support from our network of dealers. Plus, there's no cut-off time for parts and service, meaning we're available to you throughout the lifetime of your machine.

There's a pride and responsibility built into every piece of equipment we sell, and we make it our mission to keep your machine running smoothly, every single time you turn the key.

Ask your dealer about AGCO Protection, an extended warranty program that prolongs your coverage and safeguards against the cost of sudden breakdowns.

AGCO replacement parts are made to the same high standards as those used on the assembly line, so your AGCO® equipment will stay running like new. Talk to your dealer, or shop at parts.agcocorp.com to find the AGCO Genuine Parts you need.

Focus on your operation, not on scheduling maintenance. With AGCO GenuineCare plans, your service intervals are predetermined. You'll avoid downtime and be able to better plan your costs thanks to transparent pricing, bundles and discounts.







TECHNICAL SPECIFICATIONS

MODELS		2604 H	2605 H	2606 H	2607 H
		2004 H	2005 H	2000 H	2007 Π
Engine Poted anging power	HP (kW)	4E (22 G)	EE (41 O)	GE (40 0)	74 (EE 1)
Rated engine power		45 (33.6)	55 (41.0)	65 (48.8)	74 (55.1)
Rated engine speed	rpm HP (kW)	38 (30.1)	46 (33.8)	55 (40.4)	C4 (47)
Rated PTO power	TP (KW)	36 (30.1)	, ,		64 (47)
Engine Air and fuel systems		Simpson 2.6 L, 3-cylinder, Tier 4 final-compliant Intercooler turbo-charged with electronically controlled high-pressure common rail fuel injection			
Emission control		External cooled exhaust gas recirculation (EGR) with diesel oxidation catalyst (DOC)			
Drivetrain			External cooled exhaust gas recirculation	(EGR) with dieser oxidation catalyst (DOC)
Drivetrain					
Mechanical transmission		8F x 2R SideShift	2WD — 8F x 2R SideShift 4WD — 8F x 8R Synchro Shuttle	8F x 8R Synchro Shuttle	
Main clutch		Dual dry		Split torque clutch	
Rear axle		Direc	Direct drive Outboard planetary		planetary
Brakes		Drum brakes		Oil-immersed wet disc	
Differential lock		Mechanical engagement via right-side heel pedal			
Front axle		2WD straight adjustable / 4WD planetary reduction			
4WD engagement	17. 2.1	Mechanical via push-pull lever in platform to left of seat			
Hydraulics					
Hydraulic system	3-1-1-1-1	Massey Ferguson hydraulics, Mark 1A scotch yoke piston pump			
Hydraulic flow @ remote	GPM (LPM)	10.6 (40.1)			
Total hydraulic flow	GPM (LPM)	15.7 (59.5)			
Remote valves		One standard, two optional Two standard			
3-point lift capacity @ pins	lbs. (kg)	3,747 (1,700)	4,519 (2,050)		
3-point lift capacity @ 24" behind	lbs. (kg)	2,204 (1,000) 2,755 (1,250)			
Rear PTO		2WD & 4WD — live	2WD — live 4WD — independent	2WD & 4WD — independent	
Operator Area					
Platform features		Debris/heat shield, rubber floormat			
Seat and steering		ReverseRise adjustable seat w/ fixed steering column			
Dimensions					
Overall length	in. (mm)	2WD — 138 (3,510); 4WD — 139 (3,526)			
Wheelbase	in. (mm)	2WD — 80.7 (2,070); 4WD — 81.5 (2,050)			
Overall width	in. (mm)	64.6 (1,641)	66.5 (1,689)	69.9 (1,775)	72.9 (1,851)
Overall height	in. (mm)	90.6 (2,300)	91.3 (2,320)	93.9 (2,385)	94.5 (2,400)
		2WD — 4,597 (2,085)	2WD — 4,894 (2,220)	2WD — 5,115 (2,320)	2WD — 5,269 (2,390)
ROPS base weight without ballast	lbs. (kg)	4WD — 4,927 (2,235)	4WD — 5,394 (2,446)	4WD — 5,710 (2,590)	4WD — 5,864 (2,660



APPLY NOW FOR PRE-APPROVAL www.masseyferguson.com



or scan the QR code to get started.



*Currently only available for individual applicants. Subject to credit review and approval and other terms and conditions. All financing is in AGCO Finance LLC's sole discretion.

©2022 AGCO Corporation. Massey Ferguson is a worldwide brand of AGCO Corporation.

AGCO and Massey Ferguson are trademarks of AGCO. All rights reserved. I MF22B006FC

MASSEY FERGUSON

BORN TO